



SNOWDECOR SCRATCH FINISH

SCOPE

Contains acrylic copolymer emulsion and reinforced with high quality marble powder & silica sand and its aggregates. It is formulated to withstand humidity, rain & hot climatic condition. It contains anti bacterial & anti fungal additives.

Texture finishes available-

- **ONYX**- 2.0 mm scratch finish.
- **CRYSTAL**- 1.0 mm scratch finish.
- **QUARTZ**- 0.5 mm scratch finish.

AREAS OF APPLICATION

SNOWDECOR adheres perfectly to different external & internal surfaces, like plaster, masonry, brickwork, concrete, gypsum & asbestos. It is also reviving old surfaces.

SURFACE PREPARATION

PLASTER

New masonry surfaces must be allowed to cure completely. Recommended curing time is 28 days minimum.



CLEANING

Surface must be cleaned and sound, free from all dust, oil, grease and other contaminations. Remove all loose material with scrapper or stiff wire brush. Dampness of the wall has to be treated with appropriate measures.



APPLICATION PROCEDURE

Mix the paste properly. Add water if required. Apply by trowel.

PRECAUTIONS

Texture finish to be applied on a painted surface, a coat of SNOWSOL Stabilizing Solution is recommended. Texture finish should not be applied on wet surfaces. Avoid touch up work on texture finish, as faults could be visible. For better results, SNOWDECOR should be applied by skill labour only.

HANDLING & STORAGE

Keep containers/sacks airtight during handling and storage to avoid loss of material. Store **SNOWDECOR** in a cool dry place and also protect it from extreme climatic conditions during storage, in transit and at site.

POST PAINTING CARE

Apply 1 coat of Primer and 2 coats of exterior emulsion paint over texture finish.

DISCLAIMER

The information contained within this data sheet is based on information believed to be reliable at the time of its preparation. The company will not be liable for loss or damage howsoever caused including liability for negligence, which may be suffered by the user of the data contained herein. It is the users' responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.

Corporate office:

3rd Floor, Agrima Business Centre, N. K. Mehta International House, 178, Backbay Reclamation, Babubhai Chinai Marg, Mumbai - 400 020. Maharashtra, India.

Branches:

Ahmedabad | Bangalore | Ghaziabad | Jaipur | Kochi | Kolkata | Mumbai | New Delhi | Pune | Secunderabad

CFA Locations:

Cuttack | Indore | Jamshedpur | Kanpur | Nagpur | Raipur | Salem | Visakhapatnam

Eco-friendly Commitment: All products of Snowcem Paints are Lead, Chromium and Mercury free

Please consider the environment before printing it.

Colour	Base Colour
Finish	Textured Scratch Finish
Solids (%)	ONYX: 88 ± 2 CRYSTAL: 84 ± 2 QUARTZ: 83 ± 2
Theoretical coverage ONYX 2mm	
Sq.ft./kg/coat:	2.6 - 2.8
Sq.mtr./kg/coat	0.21 - 0.22
Recommended DFT:	2.0-2.2 mm
CRYSTAL 1mm	
Sq.ft./kg/coat:	2.6 - 3.6
Sq.mtr./kg/coat	0.21 - 0.33
Recommended DFT:	1.0-1.2 mm
QUARTZ 0.5mm	
Sq.ft./kg/coat:	3.3 - 4.0
Sq.mtr./kg/coat	0.30 - 0.37
Recommended DFT:	0.6 - 0.8 mm
Mode Of Application	Trowel
Recommended System	One coat of scratch finish, one coat of primer and two coats of acrylic exterior paint

AVAILABLE PACK SIZES

Available in 30 kg sacks.

All our packing has Snowcem Paints Hologram, a mark of genuineness.

