



SNOWCARE WALL PUTTY

EXTERIOR/INTERIOR WALL PUTTY

PRODUCT DESCRIPTION

SNOWCARE WALL PUTTY is a combination of high quality white Portland cement, natural minerals, special additives & polymers. It is specially manufactured to impart toughness, durability, binding, waterproofing and longer life to exterior and interior surfaces. SNOWCARE hides the minor imperfections of the surface and prevents hairline cracks to appear on the surface.

SURFACE PREPARATION

PLASTER

New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.



CLEANING

Ensure the surface is completely free from all dirt, loosely held plaster, powdery residue, oil grease or any other contamination. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.



FILLING THE CRACKS, HOLES & DENTS

For filling cracks upto 3mm, holes and dents use white cement and fine sand in the ratio 1:3
For Interior surfaces or substrates that are subjected to continuous seepage or dampness, kindly get the repairs done before the application of paint.



PAINT APPLICATION PROCESS

APPLICATION	RECOATING PERIOD
STEP 1 SANDING	Sand the surface with emery paper 180 and wipe clean
STEP 2 PRE WET THE SURFACE	Pre wet the surface before application of 1st coat of SNOWCARE WALL PUTTY.
STEP 3 (1st Coat) SNOWCARE WALL PUTTY TROWEL/PUTTY KNIFE	Mix SNOWCARE WALL PUTTY with water 40% by volume. wait for 10 to 15 minutes. Mix it & then apply. 6 to 8 Hours. Depending upon climatic condition.
STEP 4 (2nd Coat) SNOWCARE WALL PUTTY TROWEL/PUTTY KNIFE	6 to 8 Hours. Depending upon climatic condition. Sand the surface with emery paper 320 & wipe clean.
STEP 5 APPLICATION OF PRIMER AND EMULSION COAT BRUSH / ROLLER / SPRAY	Apply a coat of PRIMER followed by 2-3 coats of emulsion paint.

Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different atmospheric conditions.

PRODUCT FEATURES

Gives Toughness To The Surface

Does Not Require Curing With Water.

Good Water Resistance.

Increases Durability Of The Surface

Provides Smooth & Uniform Finish To Rough Plasters.

Controlled Water Vapour Permeability

Fills Hair Cracks & Pinholes.

Excellent Abrasion Resistance.

Resists Growth Of Algae And Fungi On Wall.

COLOURS AVAILABLE

WHITE*

Please Note - SNOWCARE WALL PUTTY is an undercoat.



MIXING RATIO

Dilute one kg of SNOWCARE WALL PUTTY with 400 ml of clean potable water, mixed with carefully with hand or by specially equipment available in market. Wait for 10 minutes & apply with putty knife/Trowel or putty blade. Don't over dilute SNOWCARE WALL PUTTY.



COVERAGE

When mixed to proper consistency, approx. 10-12 Sq. ft. per kg. for upto 1.5 mm thickness in 2 coats. Coverage depends on surface condition/preparation and varies according to texture, suction / porosity of the surface, method of application and thickness of coat. For abundant precaution, an initial trial may be undertaken to determine covering capacity on very rough or abnormal surface.



AVAILABLE PACK SIZES

The pack sizes available for SNOWCARE WALL PUTTY are 20 kg and 5 kg, 1 kg poly bags and 40 kg for projects. All our packing has Snowcem Paints Hologram, a mark of genuineness.





SNOWCARE WALL PUTTY

EXTERIOR/INTERIOR WALL PUTTY

TECHNICAL DETAILS

Nature	White Powder
Base	White Portland cement, natural minerals & polymers.
Colour	White.
Finish	Smooth Finish.
Mode of application	Trowel, Putty Knife/blade.
Drying Time	4 hours under normal climatic conditions.
Recoating period	6 to 8 hours.
Potlife	To be used within 1 hour after mixing.

HANDLING & STORAGE

Keep sacks airtight during handling and storage to avoid loss of material. Store **SNOWCARE WALL PUTTY** in a cool dry place and also protect it from extreme climatic conditions during storage, in transit and at site.

SAFETY MEASURES

Kindly refer to the MSDS for **SNOWCARE WALL PUTTY** which gives detailed information on safety measures while handling the paint, which is available on request.

Store the material in a cool, dry place. Keep out of reach of children and away from eatables.

May be harmful if swallowed. In case of ingestion seek immediate medical attention. In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in watercourses.

In the event of spills, contain spillage using sand or earth.

POST PAINTING CARE

It is important to apply a coat of **PRIMER (EXT/INT)** over **SNOWCARE WALL PUTTY** before application of emulsion Paint.

Corporate office:

3rd Floor, Agrima Business Centre, N. K. Mehta International House, 178, Backbay Reclamation, Babubhai Chinai Marg, Mumbai - 400 020. Maharashtra, India.

Depots:

Ahmedabad | Bangalore | Chennai | Cuttack | Ghaziabad | Hyderabad | Indore | Jaipur | Kanpur | Kolhapur | Kochi | Kolkata | Mumbai | Mumbai-Thane | Nagpur | New Delhi | Pune | Rajkot | Salem | Siliguri | Vishakhapatnam

Eco-friendly Commitment: All products of Snowcem Paints are Lead, Chromium and Mercury free

Please consider the environment before printing it.



VOLATILE ORGANIC COMPOUNDS

SNOWCARE WALL PUTTY contains ZERO VOC



HEAVY METALS

SNOWCARE WALL PUTTY is free from lead, chromium (VI), cadmium, mercury and its compounds.



HAZARDOUS CHEMICALS

SNOWCARE WALL PUTTY does not contain harmful compounds like formaldehyde, phenolic compounds, benzene, etc.

